



宏立機電設備有限公司

HONG LI E&M EQUIPMENTS COMPANY LIMITED

BAUER COUPLING 鮑爾接頭

Characteristic & Application 特點及應用

Bauer couplings are designed primarily for use in irrigation, dewatering and other Industrial applications. This style of fitting is available galvanized steel in sizes ranging from 2" to 8". Bauer fittings can be coupled at offsets of up to 30 degrees depending on the diameter of the line. This benefit allows for easier installation and offers the end user greater flexibility when routing hoses and pipes.

鮑爾接頭是主要設計用於灌溉、排水和其他工業應用。此接頭常見呎吋是由 2"到 8"，材質一般為鍍鋅鋼。鮑爾接頭接合時，最高可偏移 30 度，使安裝更方便，並且在軟管佈設時為使用戶提供更大的靈活性。



Specification 產品規格

Size 呎吋	Application 可應用於
2 inch	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose 2" AW300 Rubber Hose
3 inch	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
4 inch	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
6 inch	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
8 inch	8" GORO Layflat Hose 8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用



T-Bolt Clamp
闊身喉碼



Omega Clamp
奧米茄碼