



宏立機電設備有限公司

HONG LI E&M EQUIPMENTS COMPANY LIMITED

HOSE MENDER 鍍鋅接頭

Characteristic & Application 特點及應用

Hose mender works with all standard hose systems, and is designed for hose repairs, or to connect two hoses together.

鍍鋅接頭可與所有標準軟管配合使用，此產品能用於軟管維修或將兩個軟管連接在一起。



Specification 產品規格

Size 呎吋	Application 可應用於
2 inch	2" GORO Layflat Hose 2" GORO Smooth Spiral Hose 2" GORO Heavy Duty Spiral Hose 2" WS150 Rubber Hose 2" AW300 Rubber Hose
3 inch	3" GORO Layflat Hose 3" GORO Smooth Spiral Hose 3" GORO Heavy Duty Spiral Hose 3" WS150 Rubber Hose 3" AW300 Rubber Hose
4 inch	4" GORO Layflat Hose 4" GORO Smooth Spiral Hose 4" GORO Heavy Duty Spiral Hose 4" WS150 Rubber Hose 4" WS300 Rubber Hose 4" AW300 Rubber Hose 4" CD70 Cement Discharge Hose
6 inch	6" GORO Layflat Hose 6" GORO Smooth Spiral Hose 6" GORO Corrugated Spiral Hose 6" GORO Heavy Duty Spiral Hose 6" WS150 Rubber Hose 6" WS300 Rubber Hose 6" CD70 Cement Discharge Hose
8 inch	8" GORO Layflat Hose 8" GORO Corrugated Spiral Hose 8" GORO Heavy Duty Spiral Hose 8" WS150 Rubber Hose 8" WS300 Rubber Hose 8" CD70 Cement Discharge Hose

可配合以下管件使用



T-Bolt Clamp
闊身喉碼



Omega Clamp
奧米茄碼